



Ajax LeaksProtect Flood detector

Ajax LeaksProtect detects and notifies you of an inflow of water within seconds, but automatically cancels the alarm if the area dries. Energy-efficient, reliable and extremely long lasting.



Maximum performance

Works up to 2,000 meters from Ajax Hub in open space or across several floors of a business center
Early detection of flooding



Protection from intruders and failure

Waterproof with nickel-plated contacts
Uses authentication to protect against fraud
Tampering alarm
Users are immediately notified of unexpected movement of the detector
Adjustable polling period from 12 seconds



Effortless operation

Alarms are automatically canceled if the water dries
Two-way communication with Ajax Hub allows for periodic testing and customization
Saves energy by regulating power consumption based on the distance from Ajax Hub
Has a battery life of up to 5 years



Simple professional-level installation

The quality of the connection and detection area can be tested remotely
Connects to Ajax Hub with a single click

Tech specs

- Detector type: Wireless
- Use: Indoor
- Radio signal power: 20 mW
- Communication protocol: Jeweller (868.0-868.6 MHz)
- Maximum distance between detector and central unit: Up to 2,000 m (6,552 ft) (in open area)
- Polling interval: 12-300 sec (adjustable)
- Battery type: 2 AAA
- Power supply voltage: 3 V
- Battery life: Up to 5 years
- Working temperature range: From 0°C (+32°F) to +50°C (+122°F)
- Tampering alarm: Available
- Alarm for detector's displacement: Available
- Ingress protection: IP65
- Dimensions: 56x56x14 mm (2.20x2.20x0.55 in)