


BioFace MSD50K

AI Dynamic Face Recognition
Time Attendance and Access Control Terminal



Single user
/ Multi user



Fingerprint



PIN



RFID
Support



8.0 inch
Touch Screen



Access
Control



0.5-2.5 meters
Reading Distance



Photo
Capture



Live Body
Detection



Multi
Language



Education



Retail



Government



Health



Logistics



Bank



Office



Factory

Technical Specifications

BioFace MSD50K

| | |
|---------------------------|--|
| Product name | Bioface-MSD50K Dynamic Face Recognition Terminal |
| Screen | 8.0 Inch IPS Touch Screen, HD 800*1280 |
| Keypad | Touch keypad |
| Operation system | LINUX |
| CPU, NPU | 1.2G Dual-Core ARM Cortex-A7, 600G (0.6T) |
| RAM | 256MB DDR3L |
| ROM | eMMC Flash 4GB |
| Binocular camera | Real Sensor 1/2.9 inch FOV 75° 200W pixel Sony high-definition color camera WDR wide dynamic Sensor 1/5 inch FOV 75°200W pixel infrared live camera |
| Live detection | Dynamic dual-camera anti-counterfeiting, to prevent all kinds of black &white, color photos and videos from deception |
| Logs capacity | 500000 |
| Verification | Dynamic face recognition, password, ID&IC card |
| Face capacity | 50,000 |
| Fingerprint Capacity | 1,00,000 |
| Card Capacity | 50,000(ID/IC) |
| Password Capacity | 50,000 |
| Face Recognition Accuracy | 99.70% |
| Recognition Speed | ≤0.2s, support single user/multi people(at most 5 people) recognition at same time |
| Recognition Distance | 0.5-2.5 meters (0.5-1.5 meters with live face recognition on) |
| WDR | Wide dynamic range, support accurate face recognition under Strong light, dark light and backlight Supports simultaneous recognition of up to 5 people, face tracking, face capture |
| USB | USB2.0x1, Support U disk import/export data |
| Network Communication | TCP/IP, Wifi, 4G, 4G+GPS(optional) |
| Management Software | Desktop, Cloud, SDK, Mobile APP |

Technical Specifications

BioFace MSD50K

| | |
|----------------------------|--|
| Access Control Interface | Relay output*1set, Alarm output*1set, Exit button*1set, Wiegand: input&output 26/34, Door sensor*1set |
| Environmental adaptability | Working temperature: -15C~+45°C (storage temperature -40C~+65°C), Working humidity: 20%-90% (storage humidity 20%-90+2%), |
| Multi language | Support more than 20 national languages and voices including English and other languages |
| Automatic fill light | Support infrared fill light, the white fill light automatically lights up when face is captured in dark light |
| Working Current | stand-by current: 310mA, Working current: 520mA |
| QR Code Scanner | Support |
| Mask Detection | Support |
| Power Supply | DC12V 2A |
| Installation Way | Standard: Wall mount, desktop stand; Optional: bracket for turnstile, floor stand |