

BioFace MSD5K

AI Dynamic Face Recognition Access Control



Single user / Multi user



PIN



Fingerprint



RFID Support



0.5-2.5 meters Reading Distance



2MP Colorful WDR



4.3 inch Touch Screen



Multi Language



Access Control



99.70% Recognition Accuracy



≤0.2s Recognition Speed



Education



Retail



Government



Health



Logistics



Bank



Office



Factory

Technical Specifications

BioFace MSD5K

Hardware	
CPU	1.2G Dual-Core ARM Cortex-A7
NPU	600G (0.6T)
RAM	256M DDR3L
ROM	4G EMMC
Camera	Real Sensor 1/2.9 inch FOV 75° 2MP pixel high-definition color camera WDR wide dynamic Sensor 1/5 inch FOV 75° 2MP pixel infrared live camera
Fill Light	LED Fill Light and Dual Infrared Fill Light (Automatic control according to ambient light)
Display	4.3 Inch Touch Screen, 272*480
Communication port	TCP/IP, USB-Type A(Support U disk), Wifi
Product Size	187.5mm*87.5mm*26mm
Power	DC 12V, 1A/2A
Working Temperature	0-45 °C
Working Environment	Under normal light, strong light, dark environment, backlight
Firmware Specs	
OS	Linux 3.0
Language	English and customizable
Verify Method	Face, Finger Recognition, ID Card(IC optional), Password, or combination
QR Code Scanner	Support(Scan by camera)
Face/Card/Password Capacity	5000(50,000 optional)
Fingerprint Capacity	10000
Logs Capacity	500000
Face Recognition Speed	<0.2S
Face Recognition Distance	0.5-2.5 meters(adjustable)
Live Face Detection	Reject Photo and Video
Mask Detection	Support mask detection and face recognition with wearing mask

Technical Specifications

BioFace MSD5K

Access Control Interface	
Relay output	One set
Alarm output	One set
Fire Input	One set
Door Sensor	Support
Wiegand	One set WG 26/34 Input/Output
Exit button	Support
Door Bell	Support
Anti-Pass Back	Support