



Ajax LeaksProtect Flood detector

Ajax LeaksProtect detects and notifies you of an inflow of water within seconds, but automatically cancels the alarm if the area dries. Energy-efficient, reliable and extremely long lasting.



Maximum performance

Works up to 2,000 meters from
Ajax Hub in open space or across
several floors of a business
center
Early detection of flooding



Protection from intruders and failure

Waterproof with nickel-plated
contacts
Uses authentication to protect
against fraud
Tampering alarm
Users are immediately notified
of unexpected movement of the
detector
Adjustable polling period from
12 seconds



Effortless operation

Alarms are automatically canceled if
the water dries
Two-way communication with Ajax
Hub allows for periodic testing and
customization
Saves energy by regulating power
consumption based on the distance
from Ajax Hub
Has a battery life of up to 5 years



Simple professional- level installation

The quality of the connection
and detection area can be tested
remotely
Connects to Ajax Hub with a single
click

Tech specs

- Detector type: Wireless
- Use: Indoor
- Radio signal power: 20 mW
- Communication protocol: Jeweller (868.0-868.6 MHz)
- Maximum distance between detector and central unit: Up to 2,000 m (6,552 ft) (in open area)
- Polling interval: 12-300 sec (adjustable)
- Battery type: 2 AAA
- Power supply voltage: 3 V
- Battery life: Up to 5 years
- Working temperature range: From 0°C (+32°F) to +50°C (+122°F)
- Tampering alarm: Available
- Alarm for detector's displacement: Available
- Ingress protection: IP65
- Dimensions: 56x56x14 mm (2.20x2.20x0.55 in)