

MBAS50

AADHAAR ENABLED BIOMETRIC ATTENDANCE SYSTEM

Designed for workplaces, banks, and high-security zones, MBAS50 ensures authentication with speed and precision. Strong connectivity keeps you in control, while all-day power guarantees reliability.



Face ID



Android



Camera




In-Built WiFi



3G/4G



Sensing



Aadhaar Enabled Facial Authentication



Introduction


Built for fast, secure face identification. Its powerful processor and Android 15 ensure smooth operation, while the 6.5" touchscreen offers an intuitive user experience. The 8MP camera with auto-adjusting flash enhances accuracy, even in low light. With Wi-Fi, Bluetooth, GPS, and dual SIM support, it integrates seamlessly into any setup. A long-lasting battery keeps it running all day, making secure authentication effortless and reliable.

Main Features

**4GB RAM
+ 64GB eMMC**



**2.0 GHZ Octa Core
Processor**



**Proximity + ALS Sensor
Flash LED**



**RGB LED
for Different Status and
Notification**



**6.5"
Vertical Screen**
Display with Capacitive Multi-Touch



Product Application



Aadhaar Based Biometric
Time & Attendance



School
Attendance



Canteen
Management



Public
Events



Aadhaar Enabled Facial Authentication

Specifications




Hardware

CPU	: Octa-core 2.0 GHz Processor
Memory	: 64GB storage, 4GB RAM
SD Card	: microSD (Dedicated Slot)
Operating System	: Android 15
Camera	: 8MP Front Camera
Audio	: 1W, 8 ohm Speaker
Proximity Sensor	: Detects objects up to 1.5 metre
ALS Sensor	: Ambient light sensor up to 1.5K lux
Flash	: Auto-adjustable White Light for Clear Day & Night Authentication
Battery	: 5200 mAh Li-Po (Non-Removable)



Display & Touch

Screen	: 6.5" IPS LCD
Touch	: Capacitive Multi Touch with Scratch-Resistant Protective Glass



Interface

WIFI	: Wi-Fi 802.11 a/b/g/n/ac, Dual-Band
Bluetooth	: BLE 5.0
GPS	: GPS, GLONASS, GALILEO
SIM Socket	: Dual SIM (Nano-SIM, Dual Stand-by)
Network	: GSM/HSPA/LTE



Power & Charging

Charging Port	: USB Type-C
Adapter Input	: 230V – 100V AC
Adapter Output	: 5V/2A DC


Specifications




General Parameter

Casing	: Durable ABS Plastic, Metal Finish
Operating / Storage Temperature	: 0°C to 45°C
Operating Humidity	: 10%-90% RH (Non-Condensing)
Dimensions (L x W x H)	: 197 x 98 x 25mm
Weight	: 350 grams
Mounting Type	: Wall Mount

Vertical Wide Angle



Horizontal Wide Angle



MANTRA

www.mantratec.com



MANTRA

www.mantratec.com

Support : servico@mantratec.com

Sales : sales@mantratec.com

Copyrights Mantra Softech (India) Pvt Ltd. All Rights Reserved.